

# LSK SB MODY

Claw coupling (air), MODY, with safety collar

## Properties

<b>Design</b>	MODY hose coupling
<b>Construction type</b>	with safety double nipple and safety collar
<b>Connection 1</b>	Hose connection
<b>Connection 2</b>	Claw coupling
<b>Sealing form 2</b>	Rubber sealing ring
<b>Standard</b>	DIN 3228
<b>Temp. min.</b>	-40 °C
<b>Temp. max.</b>	95 °C
<b>Material</b>	Malleable cast iron coupling head / Steel nozzle
<b>Surface</b>	electro galvanised



## Description

with safety collar, reinforced thread protection ring and new sealing ring guided on both sides.

## Item

Identification	for hose ID (mm)	Inches	Cog space (mm)	Operating pressure
LSK NW 10 SB MODY	10	3/8"	42	PN 16
LSK NW 13 SB MODY	13	1/2"	42	PN 16
LSK NW 15 SB MODY	15	5/8"	42	PN 16
LSK NW 19 SB MODY	19	3/4"	42	PN 16
LSK NW 25 SB MODY	25	1"	42	PN 16

## Accessories

LSK SDOR N Rubber ring for MODY coupling

## Spare parts

LSK SGOR N Rubber ring for MODY coupling