


Properties			
Connection 1 - 3	BSP cylindrical internal threads		
Sealing form 1 - 3	for screw-in pins with shapes A, B and if necessary E.		
Construction	Compact construction		
Bore	L shaped		
Contact travel	0°; 90°		
Temp. min.	-10 °C		
Temp. max.	80 °C		
Material	Steel housing, ball and operating shaft		
Surface	electro galvanised		





Note

Note the permissible pressure limits for the connecting elements.

Please refer to the operating instructions for ball valves.

Item							
Identification	DN*	Connecting thread	Overlap	LW (mm)	Operating pressure	AF (mm)	SF*
3 BKR 04 LK VZ	4	G 1/8" -28	negative (open)	5,0	PN 400	9	1,5
3 BKR 06 LK VZ	6	G 1/4" -19	negative (open)	6,0	PN 400	9	1,5
3 BKR 10 LK VZ	10	G 3/8" -19	negative (open)	9,0	PN 400	9	1,5
3 BKR 13 LK VZ	12	G 1/2" -14	negative (open)	11,5	PN 350	9	1,5

DN = Nominal diameter, nominal width - LW = Clearance - PN = Nominal pressure - PB = Max. operating pressure - AF = Width across flats - SF = Safety factor

Product versions

3 BKR LK 3-way ball valve in block design, burnished

Spare parts	
BK ANSCHLAG	Stop washers for ball valve
BK GEKR GRIFF SW	Handle (offset) for ball valve