

# 3 BKR ND L

3-way ball valve in low pressure design

## Properties

<b>Connection 1 - 3</b>	BSP cylindrical internal threads
<b>Sealing form 1 - 3</b>	Shape A
<b>Bore</b>	L shaped
<b>Contact travel</b>	0°; 90°
<b>Temp. range</b>	Water: 0 °C to +150 °C Air: - 20 °C to + 150 °C
<b>Material</b>	Brass housing Aluminium handle Brass ball, hard chrome-plated PTFE ball seal
<b>Surface</b>	nickel plated



## Ordering information

Other pressure and temperature figures available on request.

## Item

Identification	DN*	Connecting thread	Operating pressure (bar)
3 BKR 06 ND L	6	G 1/4" -19	25,0
3 BKR 10 ND L	10	G 3/8" -19	25,0
3 BKR 13 ND L	12	G 1/2" -14	25,0
3 BKR 20 ND L	19	G 3/4" -14	25,0
3 BKR 25 ND L	25	G 1" -11	25,0
3 BKR 32 ND L	31	G 1.1/4" -11	25,0
3 BKR 40 ND L	38	G 1.1/2" -11	25,0
3 BKR 50 ND L	50	G 2" -11	25,0

DN = Nominal diameter, nominal width