


3 BKR ND L

3-way ball valve in low pressure design

Properties

| | |
|---------------------------|---|
| Connection 1 - 3 | BSP cylindrical internal threads |
| Sealing form 1 - 3 | Shape A |
| Bore | L shaped |
| Contact travel | 0°; 90° |
| Temp. range | Water: 0 °C to +150 °C Air: - 20 °C to + 150 °C |
| Material | Brass housing Aluminium handle Brass ball, hard chrome-plated PTFE ball seal |
| Surface | nickel plated |



Ordering information

Other pressure and temperature figures available on request.

Item

| Identification | DN* | Connecting thread | Operating pressure (bar) |
|----------------|-----|-------------------|--------------------------|
| 3 BKR 06 ND L | 6 | G 1/4" -19 | 25,0 |
| 3 BKR 10 ND L | 10 | G 3/8" -19 | 25,0 |
| 3 BKR 13 ND L | 12 | G 1/2" -14 | 25,0 |
| 3 BKR 20 ND L | 19 | G 3/4" -14 | 25,0 |
| 3 BKR 25 ND L | 25 | G 1" -11 | 25,0 |
| 3 BKR 32 ND L | 31 | G 1.1/4" -11 | 25,0 |
| 3 BKR 40 ND L | 38 | G 1.1/2" -11 | 25,0 |
| 3 BKR 50 ND L | 50 | G 2" -11 | 25,0 |

DN = Nominal diameter, nominal width