


Properties			
Connection 1 - 3	BSP cylindrical internal threads		
Sealing form 1 - 3	for screw-in pins with shapes A, B and if necessary E.		
Design	3-way ball valve, in forged design		
Bore	T shaped		
Contact travel	0°; 90°		
Temp. min.	-10 °C		
Temp. max.	80 °C		
Material	Forged steel housing Steel ball and operating shaft POM ball seal NBR O-ring		
Surface	burnished		





## Note

Please refer to the operating instructions for ball valves.

Note the permissible pressure limits for the connecting elements.

Item							
Identification	DN*	Connecting thread	Overlap	LW (mm)	Operating pressure	AF (mm)	SF*
3 SKR 20 TK	19	G 3/4" -14	negative (open)	20	PN 350	14	1,5
3 SKR 25 TK	25	G 1" -11	negative (open)	24	PN 350	14	1,5

DN = Nominal diameter, nominal width - LW = Clearance - PN = Nominal pressure - PB = Max. operating pressure - AF = Width across flats - SF = Safety factor

## **Product versions**

3 SKR TK VZ 3-way ball valve, in forged design, electro galvanised

Spare parts	
BK ANSCHLAG	Stop washers for ball valve
BK GEKR GRIFF SW	Handle (offset) for ball valve