


| Properties | | | |
|--------------------|---|--|--|
| Connection 1 - 3 | BSP cylindrical internal threads | | |
| Sealing form 1 - 3 | for screw-in pins with shapes A, B and if necessary E. | | |
| Design | 3-way ball valve, in forged design | | |
| Bore | T shaped | | |
| Contact travel | 0°; 90° | | |
| Temp. min. | -10 °C | | |
| Temp. max. | 80 °C | | |
| Material | Forged steel housing Steel ball and operating shaft POM ball seal NBR O-ring | | |
| Surface | electro galvanised | | |





Note

Please refer to the operating instructions for ball valves.

Note the permissible pressure limits for the connecting elements.

| Item | | | | | | | |
|----------------|-----|-------------------|-----------------|------------|--------------------|------------|-----|
| Identification | DN* | Connecting thread | Overlap | LW (mm) | Operating pressure | AF (mm) | SF* |
| 3 SKR 20 TK VZ | 19 | G 3/4" -14 | negative (open) | 20 | PN 350 | 14 | 1,5 |
| 3 SKR 25 TK VZ | 25 | G 1" -11 | negative (open) | 24 | PN 350 | 14 | 1,5 |

DN = Nominal diameter, nominal width - LW = Clearance - PN = Nominal pressure - PB = Max. operating pressure - AF = Width across flats - SF = Safety factor

Product versions

3 SKR TK 3-way ball valve, in forged design, burnished

| Spare parts | |
|------------------|--------------------------------|
| BK ANSCHLAG | Stop washers for ball valve |
| BK GEKR GRIFF SW | Handle (offset) for ball valve |