

# 3 SKR TK VZ

3-way ball valve, in forged design

## Properties

<b>Connection 1 - 3</b>	BSP cylindrical internal threads
<b>Sealing form 1 - 3</b>	for screw-in pins with shapes A, B and if necessary E.
<b>Design</b>	3-way ball valve, in forged design
<b>Bore</b>	T shaped
<b>Contact travel</b>	0°; 90°
<b>Temp. min.</b>	-10 °C
<b>Temp. max.</b>	80 °C
<b>Material</b>	Forged steel housing Steel ball and operating shaft POM ball seal NBR O-ring
<b>Surface</b>	electro galvanised



## Note

Please refer to the operating instructions for ball valves.  
Note the permissible pressure limits for the connecting elements.

## Item

Identification	DN*	Connecting thread	Overlap	LW (mm)	Operating pressure	AF (mm)	SF*
<b>3 SKR 20 TK VZ</b>	19	G 3/4" -14	negative (open)	20	PN 350	14	1,5
<b>3 SKR 25 TK VZ</b>	25	G 1" -11	negative (open)	24	PN 350	14	1,5

DN = Nominal diameter, nominal width – LW = Clearance – PN = Nominal pressure – PB = Max. operating pressure – AF = Width across flats – SF = Safety factor

## Product versions

**3 SKR TK** 3-way ball valve, in forged design, burnished

## Spare parts

<b>BK ANSCHLAG</b>	Stop washers for ball valve
<b>BK GEKR GRIFF SW</b>	Handle (offset) for ball valve