


Properties			
Connection 1 - 4	BSP cylindrical internal threads		
Sealing form 1 - 4	for screw-in pins with shapes A, B and if necessary E		
Bore	T shaped		
Contact travel	0°; 90°; 180°		
Temp. min.	-10 °C		
Temp. max.	80 °C		
Material	Steel housing, ball and operating shaft POM ball seal NBR O-ring		
Surface	burnished		





## Note

Please refer to the operating instructions for ball valves.

Note the permissible pressure limits for the connecting elements.

Item							
Identification	DN*	Connecting thread	Overlap	LW (mm)	Operating pressure	AF (mm)	SF*
4 BKR 04 T	4	G 1/8" -28	positive (closed)	5,0	PN 500	12	1,5
4 BKR 06 T	6	G 1/4" -19	positive (closed)	6,0	PN 500	12	1,5
4 BKR 10 T	10	G 3/8" -19	positive (closed)	9,0	PN 500	14	1,5
4 BKR 13 T	12	G 1/2" -14	positive (closed)	12,5	PN 400	14	1,5
4 BKR 20 T	19	G 3/4" -14	positive (closed)	19,0	PN 400	17	1,5
4 BKR 25 T	25	G 1" -11	positive (closed)	24,0	PN 350	17	1,5
4 BKR 32 T	31	G 1.1/4" -11	positive (closed)	24,0	PN 350	17	1,5
4 BKR 40 T	38	G 1.1/2" -11	positive (closed)	36,0	PN 63	22	1,5

DN = Nominal diameter, nominal width - LW = Clearance - PN = Nominal pressure PB = Max. operating pressure - AF = Width across flats - SF = Safety factor

Spare parts	
BK ANSCHLAG	Stop washers for ball valve
<b>BK GEKR GRIFF SW</b>	Handle (offset) for ball valve