


Properties			
Connection 1 + 2	BSP cylindrical internal threads		
Sealing form 1 + 2	for screw-in pins with shapes A, B and if necessary E		
Contact travel	0°; 90°		
Temp. min.	-20 °C		
Temp. max.	60 °C		
Material	Stainless steel housing, ball and operating shaft POM ball seal NBR O-ring		





Note

Note the permissible pressure limits for the connecting elements.

Please refer to the operating instructions for ball valves.

Item						
Identification	DN*	Connecting thread	LW (mm)	Operating pressure	AF (mm)	SF*
BKR 06 VA	6	G 1/4" -19	6	PN 400	9	1,5
BKR 10 VA	10	G 3/8" -19	10	PN 400	9	1,5
BKR 13 VA	12	G 1/2" -14	13	PN 400	9	1,5
BKR 20 VA	19	G 3/4" -14	20	PN 400	14	1,5
BKR 25 VA	25	G 1" -11	24	PN 400	14	1,5
BKR 32 VA	31	G 1.1/4" -11	32	PN 400	17	1,5
BKR 40 VA	38	G 1.1/2" -11	38	PN 400	17	1,5

DN = Nominal diameter, nominal width - PN = Nominal pressure PB = Max. operating pressure - LW = Clearance - AF = Width across flats - SF = Safety factor

Product versions			
BKR	2-way ball valve in block design, burnished		
BKR VZ	2-way ball valve in block design, electro galvanised		

Accessories	
BK ANSCHLAG	Stop washers for ball valve
BK GEKR GRIFF SW	Handle (offset) for ball valve