


### Properties

Connection 1 + 2	BSP cylindrical internal threads
Sealing form 1 + 2	for screw-in pins with shapes A, B and if necessary E
Contact travel	0°; 90°
Temp. min.	-10 °C
Temp. max.	80 °C
Material	Steel housing, ball and operating shaft Polyamide ball seal NBR O-ring
Surface	electro galvanised



### Note

Please refer to the operating instructions for ball valves.

Note the permissible pressure limits for the connecting elements.

### Item

Identification	DN*	Connecting thread	LW (mm)	Operating pressure	AF (mm)	SF*
<b>BKR 04 VZ</b>	4	G 1/8" -28	5	PN 500	9	1,5
<b>BKR 06 VZ</b>	6	G 1/4" -19	6	PN 500	9	1,5
<b>BKR 10 VZ</b>	10	G 3/8" -19	10	PN 500	9	1,5
<b>BKR 13 VZ</b>	12	G 1/2" -14	13	PN 500	9	1,5
<b>BKR 20 VZ</b>	19	G 3/4" -14	20	PN 400	14	1,5
<b>BKR 25 VZ</b>	25	G 1" -11	24	PN 350	14	1,5
<b>BKR 32 VZ</b>	31	G 1 1/4" -11	24	PN 350	14	1,5
<b>BKR 40 VZ</b>	38	G 1 1/2" -11	24	PN 350	14	1,5

DN = Nominal diameter, nominal width – LW = Clearance – PN = Nominal pressure – PB = Max. operating pressure – AF = Width across flats – SF = Safety factor

### Product versions

**BKR** 2-way ball valve in block design, burnished

**BKR VA** 2-way ball valve in block design, Stainless steel housing, ball and operating shaft

### Accessories

**BK ANSCHLAG** Stop washers for ball valve

**BK GEKR GRIFF SW** Handle (offset) for ball valve