

## Properties

**Connection 1 + 2** BSP cylindrical internal threads

**Temp. min.** 0 °C

**Temp. max.** 120 °C

**Material** Brass OT 58, steel handle



## Note

The pressure figures are applicable for temperatures from 0 °C to +25 °C; at higher temperatures, pressure reductions must be taken into account.

## Ordering information

Other pressure and temperature figures available on request.

## Item

Identification	DN*	Size	Operating pressure (bar)	G1 + G2	L (mm)
MF 06 MG	6	4	16,0	G 1/4" -19	33
MF 10 MG	10	6	16,0	G 3/8" -19	41
MF 13 MG	12	8	16,0	G 1/2" -14	36
MF 20 MG	19	12	16,0	G 3/4" -14	39
MF 25 MG	25	16	16,0	G 1" -11	43
MF 32 MG	31	20	16,0	G 1.1/4" -11	48
MF 40 MG	38	24	16,0	G 1.1/2" -11	52
MF 50 MG	51	32	16,0	G 2" -11	57
MF 65 MG	60	40	16,0	G 2.1/2" -11	65
MF 75 MG	76	48	16,0	G 3" -11	75
MF 100 MG	100	64	16,0	G 4" -11	84

DN = Nominal diameter, nominal width – G1 + G2 = Threads of connections 1+2

## Product versions

**MF VA** Sliding socket, Stainless steel