1 OK VA

1-ear clamp

HANSA-FLEX

Properties

Application	Hose mountings in low pressure range
Material	Stainless steel



Item

Identification	Clamping range (mm)	Band width (mm)
1 OK 2.9-3.3-3 VA	2,7 - 3,3	3,0
1 OK 3.0-3.5-3 VA	3,0 - 3,5	3,0
1 OK 3.3-4.1-4 VA	3,3 - 4,1	4,0
1 OK 4.1-5.1-4 VA	4,1 - 5,1	4,0
1 OK 5.1-6.1-4 VA	5,1 - 6,1	4,0
1 OK 5.6-6.6-4 VA	5,6 - 6,6	4,0
1 OK 6.1-7.0-4 VA	6,1 - 7,0	5,0
1 OK 6.5-7.5-5 VA	6,5 - 7,5	5,0
1 OK 6.8-8.0-5 VA	6,8 - 8,3	5,0
1 OK 7.1-8.3-5 VA	7,1 - 8,3	5,0
1 OK 7.5-8.7-5 VA	7,5 - 8,7	5,0
1 OK 7.5-9.0-6 VA	7,5 - 9,0	6,0
1 OK 8.1-9.5-6 VA	8,1 - 9,5	6,0
1 OK 8.5-10.0-6 VA	8,5 - 10,0	6,0
1 OK 9.1-10.5-6 VA	9,1 - 10,5	6,0
1 OK 9.3-11.0-6 VA	9,3 - 11,0	6,0
1 OK 9.6-11.3-6 VA	9,6 - 11,3	6,0
1 OK 09-11 VA	9,0 - 11,0	6,5
1 OK 10.1-11.8-6 VA	10,1 - 11,8	6,0
1 OK 10.1-12.0-6 VA	10,1 - 12,0	6,0
1 OK 10.3-12.3-6 VA	10,0 - 12,3	6,0
1 OK 10.8-12.8-6 VA	10,8 - 12,8	6,0
1 OK 11-13 VA	11,0 - 13,0	6,5
1 OK 11.3-13.3-6 VA	11,3 - 13,3	6,0
1 OK 11.8-13.8-6 VA	11,8 - 13,8	6,0
1 OK 12-14 VA	12,0 - 14,0	7,0
1 OK 12.0-14.0-6 VA	12,0 - 14,0	6,0
1 OK 12.5-14.5-6 VA	12,5 - 14,5	6,0
1 OK 13.0-15.0-6 VA	13,0 - 15,0	6,0
1 OK 13.5-15.5-6 VA	13,5 - 15,5	6,0
1 OK 13.8-16.0-6 VA	13,8 - 16,0	6,0
1 OK 14-16 VA	14,0 - 18,0	7,0
1 OK 14.0-16.5-6 VA	14,0 - 16,5	6,0
1 OK 14.6-16.8-6 VA	14,6 - 16,8	6,0
1 OK 15-17 VA	15,0 - 17,0	6,0
1 OK 15.3-17.5-6 VA	15,3 - 17,5	6,0
1 OK 16-18 VA	16,0 - 18,0	7,0
1 OK 16.3-18.5-6 VA	16,3 - 18,5	6,0
1 OK 17-19 VA	17,0 - 19,0	7,0
1 OK 17.2-19.5-6 VA	17,2 - 19,5	6,0
1 OK 17.7-20.0-7 VA	17,7 - 20,0	6,0
1 OK 17.9-20.7-7 VA	17,9 - 20,7	6,0
1 OK 18-20 VA	18,0 - 20,0	6,0
1 OK 18.7-21.0-7 VA	18,7 - 21,0	6,0
1 OK 19.5-21.8-7 VA	19,5 - 21,8	6,0
1 OK 19.9-22.5-7 VA	19,9 - 22,5	7,0
1 OK 21.0-23.5-7 VA	21,0 - 23,5	6,0
1 OK 21.7-24.5-7 VA	21,7 - 24,5	6,0
1 OK 22.7-25.5-7 VA	22,7 - 25,5	6,0
1 OK 23.6-26.3-7 VA	23,6 - 26,3	6,0

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.

1 OK VA
1-ear clamp

Item

Identification	Clamping range (mm)	Band width (mm)
1 OK 24.1-27.0-7 VA	24,1 - 27,0	6,0
1 OK 27.2-30.7-7 VA	27,2 - 30,7	6,0

Product versions

1 OK	1-ear clamp, Steel

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.