

# KSKL (LZ)

Hose clamp

## Properties

|                          |                     |
|--------------------------|---------------------|
| <b>Design</b>            | 2 piece hose clamps |
| <b>Construction type</b> | with loose tongues  |
| <b>Material</b>          | Malleable cast iron |
| <b>Surface</b>           | electro galvanised  |



## Item

| Identification      | Clamping range (mm) | Width (mm) | Operating pressure |
|---------------------|---------------------|------------|--------------------|
| <b>KSKL 22-29</b>   | 22 - 29             | 61,5       | PN 16              |
| <b>KSKL 28-34</b>   | 28 - 34             | 71,0       | PN 16              |
| <b>KSKL 32-40</b>   | 32 - 40             | 81,0       | PN 16              |
| <b>KSKL 39-49</b>   | 39 - 49             | 92,5       | PN 16              |
| <b>KSKL 48-60</b>   | 48 - 60             | 105,0      | PN 16              |
| <b>KSKL 60-76</b>   | 60 - 76             | 115,0      | PN 16              |
| <b>KSKL 77-94</b>   | 77 - 94             | 150,5      | PN 16              |
| <b>KSKL 94-115</b>  | 94 - 115            | 163,0      | PN 16              |
| <b>KSKL 115-145</b> | 115 - 145           | 198,0      | PN 16              |