


### Properties

|                   |                   |
|-------------------|-------------------|
| <b>Design</b>     | Single pipe clamp |
| <b>Temp. min.</b> | -30 °C            |
| <b>Temp. max.</b> | 90 °C             |
| <b>Material</b>   | Polypropylene     |



### Description

for quick installation of cables, hoses, oil and lubrication lines. Screw mounting.

### Item

| Identification | Clamp size | Ø d1<br>(mm) | External pipe Ø d2<br>(mm) | External pipe Ø d2 | B<br>(mm) | e1<br>(mm) | e2<br>(mm) | H<br>(mm) | L<br>(mm) |
|----------------|------------|--------------|----------------------------|--------------------|-----------|------------|------------|-----------|-----------|
| LBS 106        | 1          | 6,5          | 6,0                        | -                  | 14,5      | 9          | 7          | 13,5      | 23        |
| LBS 106.4      | 1          | 6,5          | 6,4                        | 1/4"               | 14,5      | 9          | 7          | 13,5      | 23        |
| LBS 108        | 1          | 6,5          | 8,0                        | -                  | 14,5      | 9          | 7          | 13,5      | 23        |
| LBS 208        | 2          | 6,5          | 8,0                        | -                  | 14,5      | 11         | 7          | 18,5      | 27        |
| LBS 209.5      | 2          | 6,5          | 9,5                        | 3/8"               | 14,5      | 11         | 7          | 18,5      | 27        |
| LBS 210        | 2          | 6,5          | 10,0                       | -                  | 14,5      | 11         | 7          | 18,5      | 27        |
| LBS 212        | 2          | 6,5          | 12,0                       | -                  | 14,5      | 11         | 7          | 18,5      | 27        |
| LBS 212.7      | 2          | 6,5          | 12,7                       | 1/2"               | 14,5      | 11         | 7          | 18,5      | 27        |
| LBS 310        | 3          | 6,5          | 10,0                       | -                  | 14,5      | 15         | 7          | 23,5      | 34        |
| LBS 312        | 3          | 6,5          | 12,0                       | -                  | 14,5      | 15         | 7          | 23,5      | 34        |
| LBS 312.7      | 3          | 6,5          | 12,7                       | 1/2"               | 14,5      | 15         | 7          | 23,5      | 34        |
| LBS 313.5      | 3          | 6,5          | 13,5                       | -                  | 14,5      | 15         | 7          | 23,5      | 34        |
| LBS 314        | 3          | 6,5          | 14,0                       | -                  | 14,5      | 15         | 7          | 23,5      | 34        |
| LBS 315        | 3          | 6,5          | 15,0                       | -                  | 14,5      | 15         | 7          | 23,5      | 34        |
| LBS 316        | 3          | 6,5          | 16,0                       | 5/8"               | 14,5      | 15         | 7          | 23,5      | 34        |
| LBS 414        | 4          | 6,5          | 14,0                       | -                  | 14,5      | 19         | 6          | 30,5      | 40        |
| LBS 415        | 4          | 6,5          | 15,0                       | -                  | 14,5      | 19         | 6          | 30,5      | 40        |
| LBS 416        | 4          | 6,5          | 16,0                       | 5/8"               | 14,5      | 19         | 6          | 30,5      | 40        |
| LBS 417.2      | 4          | 6,5          | 17,2                       | -                  | 14,5      | 19         | 6          | 30,5      | 40        |
| LBS 418        | 4          | 6,5          | 18,0                       | -                  | 14,5      | 19         | 6          | 30,5      | 40        |
| LBS 419        | 4          | 6,5          | 19,0                       | 3/4"               | 14,5      | 19         | 6          | 30,5      | 40        |
| LBS 420        | 4          | 6,5          | 20,0                       | -                  | 14,5      | 19         | 6          | 30,5      | 40        |
| LBS 421.3      | 4          | 6,5          | 21,3                       | -                  | 14,5      | 19         | 6          | 30,5      | 40        |
| LBS 422        | 4          | 6,5          | 22,0                       | -                  | 14,5      | 19         | 6          | 30,5      | 40        |

### Product versions

LBS PA Light construction PA pipe clamp, Polyamide