


Properties

| | |
|-------------------|-------------------|
| Design | Single pipe clamp |
| Temp. min. | -30 °C |
| Temp. max. | 90 °C |
| Material | Polypropylene |



Description

for quick installation of cables, hoses, oil and lubrication lines. Screw mounting.

Item

| Identification | Clamp size | Ø d1 (mm) | External pipe Ø d2 (mm) | External pipe Ø d2 | B (mm) | e1 (mm) | e2 (mm) | H (mm) | L (mm) |
|----------------|------------|--------------|----------------------------|--------------------|-----------|------------|------------|-----------|-----------|
| LBS 106 | 1 | 6,5 | 6,0 | - | 14,5 | 9 | 7 | 13,5 | 23 |
| LBS 106.4 | 1 | 6,5 | 6,4 | 1/4" | 14,5 | 9 | 7 | 13,5 | 23 |
| LBS 108 | 1 | 6,5 | 8,0 | - | 14,5 | 9 | 7 | 13,5 | 23 |
| LBS 208 | 2 | 6,5 | 8,0 | - | 14,5 | 11 | 7 | 18,5 | 27 |
| LBS 209.5 | 2 | 6,5 | 9,5 | 3/8" | 14,5 | 11 | 7 | 18,5 | 27 |
| LBS 210 | 2 | 6,5 | 10,0 | - | 14,5 | 11 | 7 | 18,5 | 27 |
| LBS 212 | 2 | 6,5 | 12,0 | - | 14,5 | 11 | 7 | 18,5 | 27 |
| LBS 212.7 | 2 | 6,5 | 12,7 | 1/2" | 14,5 | 11 | 7 | 18,5 | 27 |
| LBS 310 | 3 | 6,5 | 10,0 | - | 14,5 | 15 | 7 | 23,5 | 34 |
| LBS 312 | 3 | 6,5 | 12,0 | - | 14,5 | 15 | 7 | 23,5 | 34 |
| LBS 312.7 | 3 | 6,5 | 12,7 | 1/2" | 14,5 | 15 | 7 | 23,5 | 34 |
| LBS 313.5 | 3 | 6,5 | 13,5 | - | 14,5 | 15 | 7 | 23,5 | 34 |
| LBS 314 | 3 | 6,5 | 14,0 | - | 14,5 | 15 | 7 | 23,5 | 34 |
| LBS 315 | 3 | 6,5 | 15,0 | - | 14,5 | 15 | 7 | 23,5 | 34 |
| LBS 316 | 3 | 6,5 | 16,0 | 5/8" | 14,5 | 15 | 7 | 23,5 | 34 |
| LBS 414 | 4 | 6,5 | 14,0 | - | 14,5 | 19 | 6 | 30,5 | 40 |
| LBS 415 | 4 | 6,5 | 15,0 | - | 14,5 | 19 | 6 | 30,5 | 40 |
| LBS 416 | 4 | 6,5 | 16,0 | 5/8" | 14,5 | 19 | 6 | 30,5 | 40 |
| LBS 417.2 | 4 | 6,5 | 17,2 | - | 14,5 | 19 | 6 | 30,5 | 40 |
| LBS 418 | 4 | 6,5 | 18,0 | - | 14,5 | 19 | 6 | 30,5 | 40 |
| LBS 419 | 4 | 6,5 | 19,0 | 3/4" | 14,5 | 19 | 6 | 30,5 | 40 |
| LBS 420 | 4 | 6,5 | 20,0 | - | 14,5 | 19 | 6 | 30,5 | 40 |
| LBS 421.3 | 4 | 6,5 | 21,3 | - | 14,5 | 19 | 6 | 30,5 | 40 |
| LBS 422 | 4 | 6,5 | 22,0 | - | 14,5 | 19 | 6 | 30,5 | 40 |

Product versions

LBS PA Light construction PA pipe clamp, Polyamide