

# NRS (9 mm)

## Retaining clamp

### Properties

<b>Application</b>	for mounting pipes, hoses and cables
<b>Design</b>	Retaining clamp
<b>Construction type</b>	with rubber profile
<b>Standard</b>	DIN 3016
<b>Material</b>	Steel
<b>Surface</b>	galvanised



### Note

The rubber profile dampens vibrations and impacts and prevents scratching.

### Item

Identification	Minimum Ø (mm)	Band width (mm)	Hole Ø (mm)
NRS 06-09	6	9,0	4,5
NRS 08-09	8	9,0	4,5
NRS 10-09	10	9,0	4,5
NRS 12-09	12	9,0	4,5
NRS 14-09	14	9,0	4,5
NRS 15-09	15	9,0	4,5
NRS 16-09	16	9,0	4,5
NRS 18-09	18	9,0	4,5
NRS 20-09	20	9,0	4,5

### Product versions

NRS (12 mm)	Retaining clamp, Steel
NRS W4 (12 mm)	Retaining clamp, Chrome nickel steel (1.4301)
NRS (15 mm)	Retaining clamp, Steel
NRS W4 (15 mm)	Retaining clamp, Chrome nickel steel (1.4301)
NRS (20 mm)	Retaining clamp, Steel
NRS W4 (20 mm)	Retaining clamp, Chrome nickel steel (1.4301)
NRS (25 mm)	Retaining clamp, Steel