

NRS (9 mm)

Retaining clamp

Properties

Application	for mounting pipes, hoses and cables
Design	Retaining clamp
Construction type	with rubber profile
Standard	DIN 3016
Material	Steel
Surface	galvanised



Note

The rubber profile dampens vibrations and impacts and prevents scratching.

Item

Identification	Minimum Ø (mm)	Band width (mm)	Hole Ø (mm)
NRS 06-09	6	9,0	4,5
NRS 08-09	8	9,0	4,5
NRS 10-09	10	9,0	4,5
NRS 12-09	12	9,0	4,5
NRS 14-09	14	9,0	4,5
NRS 15-09	15	9,0	4,5
NRS 16-09	16	9,0	4,5
NRS 18-09	18	9,0	4,5
NRS 20-09	20	9,0	4,5

Product versions

NRS (12 mm)	Retaining clamp, Steel
NRS W4 (12 mm)	Retaining clamp, Chrome nickel steel (1.4301)
NRS (15 mm)	Retaining clamp, Steel
NRS W4 (15 mm)	Retaining clamp, Chrome nickel steel (1.4301)
NRS (20 mm)	Retaining clamp, Steel
NRS W4 (20 mm)	Retaining clamp, Chrome nickel steel (1.4301)
NRS (25 mm)	Retaining clamp, Steel