

# NRS (9 mm)

## Retaining clamp

### Properties

<b>Application</b>	for mounting pipes, hoses and cables
<b>Design</b>	Retaining clamp
<b>Construction type</b>	with rubber profile
<b>Standard</b>	DIN 3016
<b>Material</b>	Steel
<b>Surface</b>	galvanised



### Note

The rubber profile dampens vibrations and impacts and prevents scratching.

### Item

Identification	Minimum Ø (mm)	Band width (mm)	Hole Ø (mm)
NRS 06-09	6	9,0	4,5
NRS 08-09	8	9,0	4,5
NRS 10-09	10	9,0	4,5
NRS 12-09	12	9,0	4,5
NRS 14-09	14	9,0	4,5
NRS 15-09	15	9,0	4,5
NRS 16-09	16	9,0	4,5
NRS 18-09	18	9,0	4,5
NRS 20-09	20	9,0	4,5

### Product versions

<b>NRS (12 mm)</b>	Retaining clamp, Steel
<b>NRS W4 (12 mm)</b>	Retaining clamp, Chrome nickel steel (1.4301)
<b>NRS (15 mm)</b>	Retaining clamp, Steel
<b>NRS W4 (15 mm)</b>	Retaining clamp, Chrome nickel steel (1.4301)
<b>NRS (20 mm)</b>	Retaining clamp, Steel
<b>NRS W4 (20 mm)</b>	Retaining clamp, Chrome nickel steel (1.4301)
<b>NRS (25 mm)</b>	Retaining clamp, Steel