

NRS (9 mm)

Retaining clamp

Properties

| | |
|--------------------------|--------------------------------------|
| Application | for mounting pipes, hoses and cables |
| Design | Retaining clamp |
| Construction type | with rubber profile |
| Standard | DIN 3016 |
| Material | Steel |
| Surface | galvanised |



Note

The rubber profile dampens vibrations and impacts and prevents scratching.

Item

| Identification | Minimum Ø (mm) | Band width (mm) | Hole Ø (mm) |
|----------------|-------------------|--------------------|----------------|
| NRS 06-09 | 6 | 9,0 | 4,5 |
| NRS 08-09 | 8 | 9,0 | 4,5 |
| NRS 10-09 | 10 | 9,0 | 4,5 |
| NRS 12-09 | 12 | 9,0 | 4,5 |
| NRS 14-09 | 14 | 9,0 | 4,5 |
| NRS 15-09 | 15 | 9,0 | 4,5 |
| NRS 16-09 | 16 | 9,0 | 4,5 |
| NRS 18-09 | 18 | 9,0 | 4,5 |
| NRS 20-09 | 20 | 9,0 | 4,5 |

Product versions

| | |
|----------------|---|
| NRS (12 mm) | Retaining clamp, Steel |
| NRS W4 (12 mm) | Retaining clamp, Chrome nickel steel (1.4301) |
| NRS (15 mm) | Retaining clamp, Steel |
| NRS W4 (15 mm) | Retaining clamp, Chrome nickel steel (1.4301) |
| NRS (20 mm) | Retaining clamp, Steel |
| NRS W4 (20 mm) | Retaining clamp, Chrome nickel steel (1.4301) |
| NRS (25 mm) | Retaining clamp, Steel |