

NRS (12 mm)

Retaining clamp

Properties

| | |
|--------------------------|--------------------------------------|
| Application | for mounting pipes, hoses and cables |
| Design | Pipe clamp |
| Construction type | with rubber profile |
| Standard | DIN 3016 |
| Material | Steel |
| Surface | galvanised |



Note

The rubber profile dampens vibrations and impacts and prevents scratching.

Item

| Identification | Minimum Ø (mm) | Band width (mm) | Hole Ø (mm) |
|----------------|-------------------|--------------------|----------------|
| NRS 05-12 | 5 | 12,0 | 5,3 |
| NRS 06-12 | 6 | 12,0 | 5,3 |
| NRS 07-12 | 7 | 12,0 | 5,3 |
| NRS 08-12 | 8 | 12,0 | 5,3 |
| NRS 09-12 | 9 | 12,0 | 5,3 |
| NRS 10-12 | 10 | 12,0 | 5,3 |
| NRS 11-12 | 11 | 12,0 | 5,3 |
| NRS 12-12 | 12 | 12,0 | 5,3 |
| NRS 13-12 | 13 | 12,0 | 5,3 |
| NRS 14-12 | 14 | 12,0 | 5,3 |
| NRS 15-12 | 15 | 12,0 | 5,3 |
| NRS 16-12 | 16 | 12,0 | 5,3 |
| NRS 17-12 | 17 | 12,0 | 5,3 |
| NRS 18-12 | 18 | 12,0 | 5,3 |
| NRS 19-12 | 19 | 12,0 | 5,3 |
| NRS 20-12 | 20 | 12,0 | 5,3 |
| NRS 21-12 | 21 | 12,0 | 5,3 |
| NRS 22-12 | 22 | 12,0 | 5,3 |
| NRS 23-12 | 23 | 12,0 | 5,3 |
| NRS 24-12 | 24 | 12,0 | 5,3 |
| NRS 25-12 | 25 | 12,0 | 5,3 |
| NRS 50-12 | 50 | 12,0 | 5,3 |

Product versions

| | |
|-----------------------|---|
| NRS W4 (12 mm) | Retaining clamp, Chrome nickel steel (1.4301) |
| NRS (9 mm) | Retaining clamp, Steel |
| NRS (15 mm) | Retaining clamp, Steel |
| NRS W4 (15 mm) | Retaining clamp, Chrome nickel steel (1.4301) |
| NRS (20 mm) | Retaining clamp, Steel |
| NRS W4 (20 mm) | Retaining clamp, Chrome nickel steel (1.4301) |
| NRS (25 mm) | Retaining clamp, Steel |