NRS W4 (12 mm)
Retaining clamp

HANSA-FLEX

Properties

Application	for mounting pipes, hoses and cables
Design	Retaining clamp
Construction type	with rubber profile
Standard	DIN 3016
Material	Chrome nickel steel (1.4301)



Item

Identification	Minimum Ø (mm)	Band width (mm)	Hole Ø (mm)
NRS 05-12 W4	5	12,0	5,3
NRS 06-12 W4	6	12,0	5,3
NRS 07-12 W4	7	12,0	5,3
NRS 08-12 W4	8	12,0	5,3
NRS 09-12 W4	9	12,0	5,3
NRS 10-12 W4	10	12,0	5,3
NRS 11-12 W4	11	12,0	5,3
NRS 12-12 W4	12	12,0	5,3
NRS 13-12 W4	13	12,0	5,3
NRS 14-12 W4	14	12,0	5,3
NRS 15-12 W4	15	12,0	5,3
NRS 16-12 W4	16	12,0	5,3
NRS 17-12 W4	17	12,0	5,3
NRS 18-12 W4	18	12,0	5,3
NRS 19-12 W4	19	12,0	5,3
NRS 20-12 W4	20	12,0	5,3
NRS 21-12 W4	21	12,0	5,3
NRS 22-12 W4	22	12,0	5,3
NRS 23-12 W4	23	12,0	5,3
NRS 24-12 W4	24	12,0	5,3
NRS 25-12 W4	25	12,0	5,3

Product versions

NRS (12 mm)	Retaining clamp, Steel
NRS (9 mm)	Retaining clamp, Steel
NRS (15 mm)	Retaining clamp, Steel
NRS W4 (15 mm)	Retaining clamp, Chrome nickel steel (1.4301)
NRS (20 mm)	Retaining clamp, Steel
NRS W4 (20 mm)	Retaining clamp, Chrome nickel steel (1.4301)
NRS (25 mm)	Retaining clamp, Steel

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.