

# NRS (20 mm)

## Retaining clamp

### Properties

**Application** for mounting pipes, hoses and cables

**Design** Pipe clamp

**Construction type** with rubber profile

**Standard** DIN 3016

**Material** Steel

**Surface** galvanised



### Note

The rubber profile dampens vibrations and impacts and prevents scratching.

### Item

Identification	Minimum Ø (mm)	Band width (mm)	Hole Ø (mm)
NRS 10-20	10	20,0	8,4
NRS 11-20	11	20,0	8,4
NRS 12-20	12	20,0	8,4
NRS 13-20	13	20,0	8,4
NRS 14-20	14	20,0	8,4
NRS 15-20	15	20,0	8,4
NRS 16-20	16	20,0	8,4
NRS 17-20	17	20,0	8,4
NRS 18-20	18	20,0	8,4
NRS 19-20	19	20,0	8,4
NRS 20-20	20	20,0	8,4
NRS 21-20	21	20,0	8,4
NRS 22-20	22	20,0	8,4
NRS 23-20	23	20,0	8,4
NRS 24-20	24	20,0	8,4
NRS 25-20	25	20,0	8,4
NRS 26-20	26	20,0	8,4
NRS 27-20	27	20,0	8,4
NRS 28-20	28	20,0	8,4
NRS 29-20	29	20,0	8,4
NRS 30-20	30	20,0	8,4
NRS 31-20	31	20,0	8,4
NRS 32-20	32	20,0	8,4
NRS 33-20	33	20,0	8,4
NRS 34-20	34	20,0	8,4
NRS 35-20	35	20,0	8,4
NRS 36-20	36	20,0	8,4
NRS 37-20	37	20,0	8,4
NRS 38-20	38	20,0	8,4
NRS 39-20	39	20,0	8,4
NRS 40-20	40	20,0	8,4
NRS 41-20	41	20,0	8,4
NRS 42-20	42	20,0	8,4
NRS 43-20	43	20,0	8,4
NRS 44-20	44	20,0	8,4
NRS 45-20	45	20,0	8,4
NRS 46-20	46	20,0	8,4
NRS 47-20	47	20,0	8,4
NRS 48-20	48	20,0	8,4
NRS 49-20	49	20,0	8,4
NRS 50-20	50	20,0	8,4
NRS 51-20	51	20,0	8,4
NRS 54-20	54	20,0	8,4
NRS 57-20	57	20,0	8,4
NRS 60-20	60	20,0	8,4
NRS 65-20	64	20,0	8,4



# NRS (20 mm)

## Retaining clamp

### Item

Identification	Minimum Ø (mm)	Band width (mm)	Hole Ø (mm)
NRS 80-20	80	20,0	8,4
NRS 90-20	90	20,0	8,4
NRS 118-20	118	20,0	8,4

### Product versions

NRS W4 (20 mm)	Retaining clamp, Chrome nickel steel (1.4301)
NRS (9 mm)	Retaining clamp, Steel
NRS (12 mm)	Retaining clamp, Steel
NRS W4 (12 mm)	Retaining clamp, Chrome nickel steel (1.4301)
NRS (15 mm)	Retaining clamp, Steel
NRS W4 (15 mm)	Retaining clamp, Chrome nickel steel (1.4301)
NRS (25 mm)	Retaining clamp, Steel