

NRS (25 mm)

Retaining clamp

Properties

| | |
|--------------------------|--------------------------------------|
| Application | for mounting pipes, hoses and cables |
| Design | Pipe clamp |
| Construction type | with rubber profile |
| Standard | DIN 3016 |
| Material | Steel |
| Surface | galvanised |



Note

The rubber profile dampens vibrations and impacts and prevents scratching.

Item

| Identification | Minimum Ø (mm) | Band width (mm) | Hole Ø (mm) |
|----------------|-------------------|--------------------|----------------|
| NRS 15-25 | 15 | 25,0 | 10,5 |
| NRS 22-25 | 22 | 25,0 | 10,5 |
| NRS 30-25 | 30 | 25,0 | 10,5 |
| NRS 38-25 | 38 | 25,0 | 10,5 |
| NRS 42-25 | 42 | 25,0 | 10,5 |
| NRS 45-25 | 45 | 25,0 | 10,5 |
| NRS 46-25 | 46 | 25,0 | 10,5 |
| NRS 50-25 | 50 | 25,0 | 10,5 |
| NRS 55-25 | 55 | 25,0 | 10,5 |
| NRS 60-25 | 60 | 25,0 | 10,5 |
| NRS 65-25 | 65 | 25,0 | 10,5 |
| NRS 67-25 | 67 | 25,0 | 10,5 |
| NRS 68-25 | 68 | 25,0 | 10,5 |
| NRS 70-25 | 70 | 25,0 | 10,5 |
| NRS 72-25 | 72 | 25,0 | 10,5 |
| NRS 74-25 | 74 | 25,0 | 10,5 |
| NRS 125-25 | 125 | 25,0 | 10,5 |

Product versions

| | |
|----------------|---|
| NRS (9 mm) | Retaining clamp, Steel |
| NRS (12 mm) | Retaining clamp, Steel |
| NRS W4 (12 mm) | Retaining clamp, Chrome nickel steel (1.4301) |
| NRS (15 mm) | Retaining clamp, Steel |
| NRS W4 (15 mm) | Retaining clamp, Chrome nickel steel (1.4301) |
| NRS (20 mm) | Retaining clamp, Steel |
| NRS W4 (20 mm) | Retaining clamp, Chrome nickel steel (1.4301) |