NRS (25 mm)
Retaining clamp

Properties

Application	for mounting pipes, hoses and cables
Design	Pipe clamp
Construction type	with rubber profile
Standard	DIN 3016
Material	Steel
Surface	galvanised



Note

The rubber profile dampens vibrations and impacts and prevents scratching.

Item

Identification	Minimum Ø (mm)	Band width (mm)	Hole Ø (mm)
NRS 15-25	15	25,0	10,5
NRS 22-25	22	25,0	10,5
NRS 30-25	30	25,0	10,5
NRS 38-25	38	25,0	10,5
NRS 42-25	42	25,0	10,5
NRS 45-25	45	25,0	10,5
NRS 46-25	46	25,0	10,5
NRS 50-25	50	25,0	10,5
NRS 55-25	55	25,0	10,5
NRS 60-25	60	25,0	10,5
NRS 65-25	65	25,0	10,5
NRS 67-25	67	25,0	10,5
NRS 68-25	68	25,0	10,5
NRS 70-25	70	25,0	10,5
NRS 72-25	72	25,0	10,5
NRS 74-25	74	25,0	10,5
NRS 125-25	125	25,0	10,5

Product versions

NRS (9 mm)	Retaining clamp, Steel
NRS (12 mm)	Retaining clamp, Steel
NRS W4 (12 mm)	Retaining clamp, Chrome nickel steel (1.4301)
NRS (15 mm)	Retaining clamp, Steel
NRS W4 (15 mm)	Retaining clamp, Chrome nickel steel (1.4301)
NRS (20 mm)	Retaining clamp, Steel
NRS W4 (20 mm)	Retaining clamp, Chrome nickel steel (1.4301)

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.