

# K 41-14 - K 41-40

## Reducing connecting fitting

### Properties

<b>Connection 1</b>	metric cylindrical outer thread
<b>Sealing form 1</b>	Butt construction
<b>Connection 2</b>	metric cylindrical outer thread
<b>Sealing form 2</b>	24° inner cone
<b>Design</b>	Reducing connecting fitting
<b>Construction</b>	straight
<b>Scope of supply</b>	with union nut, cutting ring, pressure ring and sealing ring.
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



### Item

Identification	d3 (mm)	Ø d2 (mm)	L1 (mm)	AF (mm)	S1	S2
<b>K 41-14</b>	15	10	59	27	19	17
<b>K 41-17</b>	15	8	58	27	17	27
<b>K 41-19</b>	15	6	58	27	14	27
<b>K 41-25</b>	15	12	59	27	22	27
<b>K 41-37</b>	16	6	58	27	14	27
<b>K 41-38</b>	16	8	58	27	17	27
<b>K 41-39</b>	16	10	59	27	19	27
<b>K 41-40</b>	16	12	59	27	22	27

SW, S1, S2 = With across flats – d2, d3 = for external pipe diameter

### Product versions

**K 420-31 - K 420-88** Screw-in sockets, Steel