

# K 410-05 - K 410-09

Connection reducing socket

## Properties

**Connection 1 + 2** metric cylindrical outer thread

**Sealing form 1 + 2** Butt construction

**Design** Connecting reducing fittings

**Construction** straight

**Material** Steel

**Surface** electro galvanised



## Item

| Identification  | G1         | G2         | i1<br>(mm) | i2<br>(mm) | L1<br>(mm) | AF<br>(mm) |
|-----------------|------------|------------|------------|------------|------------|------------|
| <b>K 410-05</b> | M 18 x 1.5 | M 18 x 1.5 | 12         | 12         | 30         | 22         |
| <b>K 410-06</b> | M 22 x 1.5 | M 18 x 1.5 | 12         | 12         | 30         | 27         |
| <b>K 410-07</b> | M 22 x 1.5 | M 22 x 1.5 | 12         | 12         | 30         | 27         |
| <b>K 410-08</b> | M 22 x 1.5 | M 26 x 1.5 | 12         | 12         | 30         | 32         |
| <b>K 410-09</b> | M 26 x 1.5 | M 26 x 1.5 | 12         | 12         | 30         | 32         |

AF = Width across flats

## Product versions

**K 41-07 - K 41-35** Connecting fitting, with union nut, cutting ring, pressure ring and sealing ring.

**K 42-18 - K 42-129** Screw in fitting, with union nut, cutting ring, pressure ring and sealing ring.