

K 410-05 - K 410-09

Connection reducing socket

Properties

Connection 1 + 2 metric cylindrical outer thread

Sealing form 1 + 2 Butt construction

Design Connecting reducing fittings

Construction straight

Material Steel

Surface electro galvanised



Item

| Identification | G1 | G2 | i1 (mm) | i2 (mm) | L1 (mm) | AF (mm) |
|-----------------|------------|------------|------------|------------|------------|------------|
| K 410-05 | M 18 x 1.5 | M 18 x 1.5 | 12 | 12 | 30 | 22 |
| K 410-06 | M 22 x 1.5 | M 18 x 1.5 | 12 | 12 | 30 | 27 |
| K 410-07 | M 22 x 1.5 | M 22 x 1.5 | 12 | 12 | 30 | 27 |
| K 410-08 | M 22 x 1.5 | M 26 x 1.5 | 12 | 12 | 30 | 32 |
| K 410-09 | M 26 x 1.5 | M 26 x 1.5 | 12 | 12 | 30 | 32 |

AF = Width across flats

Product versions

K 41-07 - K 41-35 Connecting fitting, with union nut, cutting ring, pressure ring and sealing ring.

K 42-18 - K 42-129 Screw in fitting, with union nut, cutting ring, pressure ring and sealing ring.