

K 42-18 - K 42-129

Screw in fitting

HANSA FLEX

Properties

Connection 1 + 2	metric cylindrical outer thread
Sealing form 1 + 2	Butt construction
Construction	straight
Scope of supply	with union nut, cutting ring, pressure ring and sealing ring.
Material	Steel
Surface	electro galvanised



Item						
Identification	Ø d2 (mm)	G1	i (mm)	L1 (mm)	AF (mm)	S1
K 42-18	10	M 18 x 1.5	12	52	22	22
K 42-35	15	M 26 x 1.5	12	52	32	27
K 42-22	10	M 22 x 1.5	12	52	27	22
K 42-29	15	M 16 x 1.5	12	52	24	27
K 42-32	15	M 18 x 1.5	12	52	27	27
K 42-33	15	M 22 x 1.5	12	52	27	27
K 42-41	18	M 26 x 1.5	12	52	32	32
K 42-42	18	M 26 x 1.5	12	52	32	32
K 42-54	15	M 12 x 1.5	10	50	27	27
K 42-112	16	M 22 x 1.5	12	52	27	27
K 42-125	15	M 16 x 1.5	11	51	27	27
K 42-129	18	M 22 x 1.5	12	52	32	32

AF = Width across flats

Product versions

K 410-05 - K 410-09	Connection reducing socket, Steel
----------------------------	-----------------------------------