

# K 420-31 - K 420-88

## Screw-in sockets

### Properties

**Connection 1** metric cylindrical outer thread

**Sealing form 1** 24° inner cone

**Connection 2** metric cylindrical outer thread

**Sealing form 2** Butt construction

**Design** Screw-in sockets

**Construction** straight

**Material** Steel

**Surface** electro galvanised



### Item

Identification	Ø d2 (mm)	G1	G2	i1 (mm)	i2 (mm)	L1 (mm)	AF (mm)
K 420-76	6	M 12 x 1.5	M 16 x 1.5	10	12	28	22
K 420-77	6	M 12 x 1.5	M 22 x 1.5	10	12	28	27
K 420-78	8	M 14 x 1.5	M 16 x 1.5	10	12	28	22
K 420-79	8	M 14 x 1.5	M 22 x 1.5	10	12	28	27
K 420-80	10	M 16 x 1.5	M 22 x 1.5	11	12	29	27
K 420-81	12	M 18 x 1.5	M 22 x 1.5	11	12	29	27
K 420-88	10	M 16 x 1.5	M 16 x 1.5	11	12	29	22

AF = Width across flats

### Product versions

K 42-02 - K 42-106	Screw in fitting, with union nut and cutting ring
K 41-14 - K 41-40	Reducing connecting fitting, with union nut, cutting ring, pressure ring and sealing ring.
K 46-12-1 / K 46-12-2	Screw-in socket with test connection, Steel