

# K 420-31 - K 420-88

## Screw-in sockets

### Properties

<b>Connection 1</b>	metric cylindrical outer thread
<b>Sealing form 1</b>	24° inner cone
<b>Connection 2</b>	metric cylindrical outer thread
<b>Sealing form 2</b>	Butt construction
<b>Design</b>	Screw-in sockets
<b>Construction</b>	straight
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



### Item

Identification	Ø d2 (mm)	G1	G2	i1 (mm)	i2 (mm)	L1 (mm)	AF (mm)
<b>K 420-76</b>	6	M 12 x 1.5	M 16 x 1.5	10	12	28	22
<b>K 420-77</b>	6	M 12 x 1.5	M 22 x 1.5	10	12	28	27
<b>K 420-78</b>	8	M 14 x 1.5	M 16 x 1.5	10	12	28	22
<b>K 420-79</b>	8	M 14 x 1.5	M 22 x 1.5	10	12	28	27
<b>K 420-80</b>	10	M 16 x 1.5	M 22 x 1.5	11	12	29	27
<b>K 420-81</b>	12	M 18 x 1.5	M 22 x 1.5	11	12	29	27
<b>K 420-88</b>	10	M 16 x 1.5	M 16 x 1.5	11	12	29	22

AF = Width across flats

### Product versions

<b>K 42-02 - K 42-106</b>	Screw in fitting, with union nut and cutting ring
<b>K 41-14 - K 41-40</b>	Reducing connecting fitting, with union nut, cutting ring, pressure ring and sealing ring.
<b>K 46-12-1 / K 46-12-2</b>	Screw-in socket with test connection, Steel