

K 43-01 - K 43-76

Screw-in fitting, angle 90°

HANSA FLEX

Properties

| | |
|------------------------|--|
| Connection 1 | metric cylindrical outer thread |
| Sealing form 1 | 24° inner cone |
| Connection 2 | metric cylindrical outer thread |
| Sealing form 2 | Butt construction |
| Design | for bulkhead mounting |
| Construction | Angle 90° |
| Scope of supply | with union nut, cutting ring and counter nut |
| Material | Steel |
| Surface | electro galvanised |



Item

| Identification | Ø d2 (mm) | G1 | G1 + G2 | G2 | i (mm) | L1 (mm) | L2 (mm) | L3 (mm) | AF (mm) | S1 | S2 |
|----------------|--------------|------------|------------|------------|-----------|------------|------------|------------|------------|----|----|
| K 43-01 | 6 | - | M 12 x 1.5 | - | 20 | 27 | 12 | 38 | 12 | 14 | 17 |
| K 43-04 | 8 | M 14 x 1.5 | - | M 12 x 1.5 | 20 | 29 | 14 | 37 | 12 | 17 | 17 |
| K 43-07 | 8 | M 14 x 1.5 | - | M 14 x 1.5 | 20 | 29 | 14 | 37 | 14 | 19 | 19 |
| K 43-08 | 10 | M 16 x 1.5 | - | M 12 x 1.5 | 20 | 32 | 17 | 38 | 14 | 19 | 17 |
| K 43-09 | 10 | M 16 x 1.5 | - | M 14 x 1.5 | 20 | 32 | 17 | 38 | 14 | 19 | 19 |
| K 43-17 | 15 | M 22 x 1.5 | - | M 22 x 1.5 | 25 | 41 | 26 | 45 | 19 | 27 | 27 |
| K 43-69 | 10 | M 16 x 1.5 | - | M 22 x 1.5 | 25 | 38 | 23 | 45 | 19 | 19 | 27 |
| K 43-75 | 12 | M 18 x 1.5 | - | M 16 x 1.5 | 25 | 32 | 17 | 45 | 17 | 22 | 22 |
| K 43-76 | 12 | M 18 x 1.5 | - | M 22 x 1.5 | 25 | 32 | 17 | 45 | 17 | 22 | 27 |

Ø d2 = External pipe diameter – AF = Width across flats

Product versions

K 430-01 - K 430-72 Screw-in socket for bulkhead fitting, Steel