K 43-01 - K 43-76

Screw-in fitting, angle 90°

HANSA-FLEX

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	24° inner cone
Connection 2	metric cylindrical outer thread
Sealing form 2	Butt construction
Design	for bulkhead mounting
Construction	Angle 90°
Scope of supply	with union nut, cutting ring and counter nut
Material	Steel
Surface	electro galvanised



Item

Identification	Ø d2 (mm)	G1	G1 + G2	G2	i (mm)	L1 (mm)	L2 (mm)	L3 (mm)	AF (mm)	S1	S2
K 43-01	6	-	M 12 x 1.5	-	20	27	12	38	12	14	17
K 43-04	8	M 14 x 1.5	-	M 12 x 1.5	20	29	14	37	12	17	17
K 43-07	8	M 14 x 1.5	-	M 14 x 1.5	20	29	14	37	14	19	19
K 43-08	10	M 16 x 1.5	-	M 12 x 1.5	20	32	17	38	14	19	17
K 43-09	10	M 16 x 1.5	-	M 14 x 1.5	20	32	17	38	14	19	19
K 43-17	15	M 22 x 1.5	-	M 22 x 1.5	25	41	26	45	19	27	27
K 43-69	10	M 16 x 1.5	-	M 22 x 1.5	25	38	23	45	19	19	27
K 43-75	12	M 18 x 1.5	-	M 16 x 1.5	25	32	17	45	17	22	22
K 43-76	12	M 18 x 1.5	-	M 22 x 1.5	25	32	17	45	17	22	27

Ø d2 = External pipe diameter – AF = Width across flats

Product versions

K 430-01 - K 430-72	Screw-in socket for bulkhead fitting, Steel

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.