

# K 43-01 - K 43-76

Screw-in fitting, angle 90°

## Properties

<b>Connection 1</b>	metric cylindrical outer thread
<b>Sealing form 1</b>	24° inner cone
<b>Connection 2</b>	metric cylindrical outer thread
<b>Sealing form 2</b>	Butt construction
<b>Design</b>	for bulkhead mounting
<b>Construction</b>	Angle 90°
<b>Scope of supply</b>	with union nut, cutting ring and counter nut
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Item

Identification	Ø d2 (mm)	G1	G1 + G2	G2	i (mm)	L1 (mm)	L2 (mm)	L3 (mm)	AF (mm)	S1	S2
K 43-01	6	-	M 12 x 1.5	-	20	27	12	38	12	14	17
K 43-04	8	M 14 x 1.5	-	M 12 x 1.5	20	29	14	37	12	17	17
K 43-07	8	M 14 x 1.5	-	M 14 x 1.5	20	29	14	37	14	19	19
K 43-08	10	M 16 x 1.5	-	M 12 x 1.5	20	32	17	38	14	19	17
K 43-09	10	M 16 x 1.5	-	M 14 x 1.5	20	32	17	38	14	19	19
K 43-17	15	M 22 x 1.5	-	M 22 x 1.5	25	41	26	45	19	27	27
K 43-69	10	M 16 x 1.5	-	M 22 x 1.5	25	38	23	45	19	19	27
K 43-75	12	M 18 x 1.5	-	M 16 x 1.5	25	32	17	45	17	22	22
K 43-76	12	M 18 x 1.5	-	M 22 x 1.5	25	32	17	45	17	22	27

Ø d2 = External pipe diameter – AF = Width across flats

## Product versions

K 430-01 - K 430-72 Screw-in socket for bulkhead fitting, Steel