K 43-20 - K 43-94

Screw-in fitting, angle 90°

Properties

Connection 1 + 2	metric cylindrical outer thread
Sealing form 1 + 2	Butt construction
Design	for bulkhead mounting
Construction	Angle 90°
Scope of supply	with union nut, cutting ring, pressure ring, sealing ring and counter nut
Material	Steel
Surface	electro galvanised



Item

Identification	Ø d2 (mm)	G1	i (mm)	L1 (mm)	L2 (mm)	AF (mm)	S1	S2
K 43-20	15	M 22 x 1.5	25	55	45	19	27	27
K 43-27	15	M 26 x 1.5	25	58	47	24	32	27
K 43-31	18	M 26 x 1.5	25	58	47	24	32	32
K 43-52	18	M 22 x 1.5	25	58	47	24	27	32
K 43-68	10	M 22 x 1.5	25	55	45	19	27	22
K 43-77	16	M 22 x 1.5	25	52	42	19	27	27
K 43-94	15	M 16 x 1.5	25	55	45	19	22	27

AF = Width across flats

Product versions

K 430-17 - K 430-86	Screw-in socket for bulkhead fitting, Steel

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.