K 43-54 / K 43-99

Screw-in fitting, angle 90°

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	24° inner cone
Connection 2	metric cylindrical outer thread
Sealing form 2	Butt construction
Construction	Angle 90°
Scope of supply	with union nut, cutting ring, counter nut, pressure ring and cord ring
Material	Steel
Surface	electro galvanised

Item

Identification	Ø d2 (mm)	G1	G2	D (mm)	i (mm)	L1 (mm)	L2 (mm)	L3 (mm)	AF (mm)	S1	S2
K 43-54	12	M 18 x 1.5	M 22 x 1.5	27	25	32	17	40	17	22	27
K 43-89	6	M 12 x 1.5	M 12 x 1.5	17	20	27	12	31	12	14	17
K 43-90	8	M 14 x 1.5	M 22 x 1.5	27	23	32	17	38	17	17	27
K 43-96	12	M 18 x 1.5	M 16 x 1.5	21	25	32	17	40	17	22	22
K 43-98	10	M 16 x 1.5	M 16 x 1.5	21	25	32	17	40	14	19	22
K 43-99	10	M 16 x 1.5	M 22 x 1.5	27	25	32	17	40	17	19	27

Ø d2 = External pipe diameter – AF = Width across flats

Product versions

K 430-68 - K 430-89	Screw-in socket for bulkhead fitting, Steel

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.