

K 430-01 - K 430-72

Screw-in socket for bulkhead fitting

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	24° inner cone
Connection 2	metric cylindrical outer thread
Sealing form 2	Butt construction
Design	for bulkhead mounting
Construction	Angle 90°
Material	Steel
Surface	electro galvanised



Item

Identification	Ø d2 (mm)	G1	G2	i (mm)	L1 (mm)	L2 (mm)	AF (mm)
K 430-01	6	M 12 x 1.5	M 12 x 1.5	20	19	38	12
K 430-04	8	M 14 x 1.5	M 12 x 1.5	20	21	29	12
K 430-08	10	M 16 x 1.5	M 12 x 1.5	20	24	38	14
K 430-09	10	M 16 x 1.5	M 14 x 1.5	20	24	38	14
K 430-16	15	M 22 x 1.5	M 22 x 1.5	25	33	45	19
K 430-23	18	M 26 x 1.5	M 22 x 1.5	25	33	47	24
K 430-55	12	M 18 x 1.5	M 16 x 1.5	25	24	45	17
K 430-56	12	M 18 x 1.5	M 22 x 1.5	25	24	45	17
K 430-72	10	M 16 x 1.5	M 22 x 1.5	25	30	45	19

Ø d2 = External pipe diameter – AF = Width across flats

Product versions

K 43-01 - K 43-76 Screw-in fitting, angle 90°, with union nut, cutting ring and counter nut