

K 430-17 - K 430-86

Screw-in socket for bulkhead fitting

Properties

Connection 1 + 2	metric cylindrical outer thread
Sealing form 1 + 2	Butt construction
Design	for bulkhead mounting
Construction	Angle 90°
Material	Steel
Surface	electro galvanised



Item

Identification	G1	G2	i (mm)	L1 (mm)	L2 (mm)	AF (mm)	Note
K 430-17	M 22 x 1.5	M 22 x 1.5	25	33	45	19	-
K 430-21	M 26 x 1.5	M 22 x 1.5	25	36	47	24	-
K 430-30	M 18 x 1.5	M 22 x 1.5	25	33	45	19	-
K 430-37	M 22 x 1.5	M 26 x 1.5	25	36	47	24	-
K 430-38	M 26 x 1.5	M 26 x 1.5	25	36	47	24	-
K 430-54	M 22 x 1.5	M 18 x 1.5	25	33	45	19	-
K 430-57	M 22 x 1.5	M 22 x 1.5	25	30	42	19	Discontinued item
K 430-86	M 16 x 1.5	M 22 x 1.5	25	-	45	19	-

AF = Width across flats

Product versions

K 43-19 - K 43-95	Screw-in socket for bulkhead fitting, with counter nut
K 43-20 - K 43-94	Screw-in fitting, angle 90°, with union nut, cutting ring, pressure ring, sealing ring and counter nut
K 43-21 - K 43-73	Fitting, bulkhead wall connection, with union nut, cutting ring, pressure ring, sealing ring and counter nut
K 47-15	Connecting fitting, angle 90°, with union nut, cutting ring, pressure ring, sealing ring, counter nut and hose fitting
K 47-16	Connecting fitting, angle 90°, with union nut, cutting ring, pressure ring, sealing ring, counter nut and hose fitting
K 47-17 / K 47-19	Connection socket, angle 90°, with union nut, sealing ring, counter nut, hose fitting