K 430-68 - K 430-89

Screw-in socket for bulkhead fitting

HANSA-FLEX

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	24° inner cone
Connection 2	metric cylindrical outer thread
Sealing form 2	Butt construction
Design	for bulkhead mounting
Construction	Angle 90°
Material	Steel
Surface	electro galvanised



Item

Identification	Ø d2 (mm)	G1	G2	i (mm)	L1 (mm)	L2 (mm)	AF (mm)
K 430-68	6	M 12 x 1.5	M 12 x 1.5	20	19	31	12
K 430-70	12	M 18 x 1.5	M 22 x 1.5	25	24	40	17
K 430-71	8	M 14 x 1.5	M 22 x 1.5	23	24	38	17
K 430-87	12	M 18 x 1.5	M 16 x 1.5	25	24	40	17
K 430-88	10	M 16 x 1.5	M 16 x 1.5	25	24	40	14

Ø d2 = External pipe diameter – AF = Width across flats

Product versions

K 43-54 / K 43-99	Screw-in fitting, angle 90°, with union nut, cutting ring, counter nut, pressure ring and cord ring

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.