

# K 430-68 - K 430-89

Screw-in socket for bulkhead fitting

## Properties

<b>Connection 1</b>	metric cylindrical outer thread
<b>Sealing form 1</b>	24° inner cone
<b>Connection 2</b>	metric cylindrical outer thread
<b>Sealing form 2</b>	Butt construction
<b>Design</b>	for bulkhead mounting
<b>Construction</b>	Angle 90°
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Item

Identification	Ø d2 (mm)	G1	G2	i (mm)	L1 (mm)	L2 (mm)	AF (mm)
<b>K 430-68</b>	6	M 12 x 1.5	M 12 x 1.5	20	19	31	12
<b>K 430-70</b>	12	M 18 x 1.5	M 22 x 1.5	25	24	40	17
<b>K 430-71</b>	8	M 14 x 1.5	M 22 x 1.5	23	24	38	17
<b>K 430-87</b>	12	M 18 x 1.5	M 16 x 1.5	25	24	40	17
<b>K 430-88</b>	10	M 16 x 1.5	M 16 x 1.5	25	24	40	14

Ø d2 = External pipe diameter – AF = Width across flats

## Product versions

**K 43-54 / K 43-99** Screw-in fitting, angle 90°, with union nut, cutting ring, counter nut, pressure ring and cord ring