

# K 44-122

## Reducing connecting fitting, T shaped

### Properties

|                           |   |
|---------------------------|---|
| <b>Connection 1</b>       | metric cylindrical outer thread   |
| <b>Sealing form 1</b>     | 24° inner cone  |
| <b>Connection 2 + 3</b>   | metric cylindrical outer thread   |
| <b>Sealing form 2 + 3</b> | Butt construction   |
| <b>Construction</b>       | T shaped  |
| <b>Scope of supply</b>    | with union nut, cutting ring, pressure ring, sealing ring and counter nut |
| <b>Material</b>           | Steel   |
| <b>Surface</b>            | electro galvanised  |



### Item

| Identification  | d3<br>(mm) | G2         | Ø d2<br>(mm) | i<br>(mm) | L1<br>(mm) | L2<br>(mm) | L3<br>(mm) | AF<br>(mm) | S1 | S2 | S3 |
|-----------------|------------|------------|--------------|-----------|------------|------------|------------|------------|----|----|----|
| <b>K 44-122</b> | 16         | M 22 x 1.5 | 6            | 24        | 43         | 32         | 34         | 19         | 27 | 14 | 27 |

AF = Width across flats

### Product versions

**K 440-80 / K 440-81** Connection socket, T shaped, Steel