

K 44-156 / K 44-162

Conection reduction fitting, T shaped

Properties

| | |
|---------------------------|--|
| Connection 1 | metric cylindrical outer thread |
| Sealing form 1 | Butt construction |
| Connection 2 + 3 | metric cylindrical outer thread |
| Sealing form 2 + 3 | 24° inner cone |
| Design | for bulkhead mounting |
| Construction | T shaped |
| Scope of supply | with union nut, cutting ring and counter nut |
| Material | Steel |
| Surface | electro galvanised |



Item

| Identification | Ø d3 (mm) | Ø d2 (mm) | L1 (mm) | L2 (mm) | L3 (mm) | L4 (mm) | L5 (mm) | L6 (mm) | L7 (mm) | AF (mm) | S1 | S2 | S3 |
|-----------------|--------------|--------------|------------|------------|------------|------------|------------|------------|------------|------------|----|----|----|
| K 44-156 | - | 12 | 24 | 56 | 32 | 17 | 20 | 29 | 44 | 17 | 22 | 22 | 24 |
| K 44-162 | 10 | 12 | 24 | 56 | 32 | 17 | 20 | 29 | 44 | 17 | 19 | 22 | 24 |

Ø d2 = External pipe diameter – AF = Width across flats

Product versions

K 440-105 / K 440-113 Connection socket, T shaped, Steel