

# K 44-164

Screw-in fitting, test connection

## Properties

|                        |  |
|------------------------|--|
| <b>Connection 1</b>    | metric cylindrical outer thread  |
| <b>Sealing form 1</b>  | with thread seal made up of pressure and cord ring                     |
| <b>Connection 2</b>    | metric cylindrical outer thread  |
| <b>Sealing form 2</b>  | 24° inner cone   |
| <b>Connection 3</b>    | metric cylindrical inner thread  |
| <b>Design</b>          | for bulkhead mounting  |
| <b>Construction</b>    | T shaped   |
| <b>Scope of supply</b> | with union nut, cutting ring, counter nut, pressure ring and cord ring |
| <b>Material</b>        | Steel  |
| <b>Surface</b>         | electro galvanised   |



## Item

| Identification  | Ø d2<br>(mm) | G1         | G2         | G3         | D<br>(mm) | i<br>(mm) | L1<br>(mm) | L2<br>(mm) | L3<br>(mm) | L4<br>(mm) | AF<br>(mm) | S1 | S2 |
|-----------------|--------------|------------|------------|------------|-----------|-----------|------------|------------|------------|------------|------------|----|----|
| <b>K 44-164</b> | 12           | M 22 x 1.5 | M 18 x 1.5 | M 12 x 1.5 | 27        | 24        | 26         | 34         | 19         | 42         | 17         | 22 | 27 |

AF = Width across flats

## Product versions

**K 440-115** Screw-in socket, T shaped, Steel