# K 44-166

Screw-in fitting, test connection, L shaped

## Properties

| | |
|---|---|
| **Connection 1** | metric cylindrical outer thread |
| **Sealing form 1** | with thread seal made up of pressure and cord ring |
| **Connection 2** | metric cylindrical inner thread |
| **Sealing form 2** | for screw-in pins with shapes A, B and if necessary E. |
| **Connection 3** | metric cylindrical outer thread |
| **Sealing form 3** | 24° inner cone |
| **Construction type** | with test connection |
| **Construction** | L shaped |
| **Scope of supply** | with union nut, cutting ring, counter nut, pressure ring and cord ring |
| **Material** | Steel |
| **Surface** | electro galvanised |



## Item

| Identification | Ø d2 (mm) | G1 | G2 | D (mm) | i (mm) | L1 (mm) | L2 (mm) | L3 (mm) | L4 (mm) | AF (mm) | S1 | S2 |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| **K 44-166** | 12 | M 22 x 1.5 | M 12 x 1.5 | 27 | 24 | 24 | 32 | 17 | 42 | 17 | 22 | 27 |

AF = Width across flats

## Product versions

| | |
|---|---|
| **K 440-116 / K440-117** | Screw-in socket, L shaped, Steel |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*