

# K 44-35 - K 44-66

Reducing connecting fitting, T shaped

## Properties

|                           |   |
|---------------------------|---|
| <b>Connection 1</b>       | metric cylindrical outer thread   |
| <b>Sealing form 1</b>     | 24° inner cone  |
| <b>Connection 2 + 3</b>   | metric cylindrical outer thread   |
| <b>Sealing form 2 + 3</b> | Butt construction   |
| <b>Construction</b>       | T shaped  |
| <b>Scope of supply</b>    | with union nut, cutting ring, pressure ring, sealing ring and counter nut |
| <b>Material</b>           | Steel   |
| <b>Surface</b>            | electro galvanised  |



## Item

| Identification | d3<br>(mm) | G1         | Ø d2<br>(mm) | i2<br>(mm) | L1<br>(mm) | L2<br>(mm) | L3<br>(mm) | AF<br>(mm) | S1 | S2 | S3 |
|----------------|------------|------------|--------------|------------|------------|------------|------------|------------|----|----|----|
| <b>K 44-35</b> | 15         | M 22 x 1.5 | 10           | 25         | 42         | 33         | 33         | 27         | 27 | 19 | 27 |
| <b>K 44-51</b> | 15         | M 22 x 1.5 | 6            | 25         | 42         | 33         | 33         | 27         | 27 | 14 | 27 |
| <b>K 44-66</b> | 18         | M 22 x 1.5 | 6            | 25         | 45         | 33         | 33         | 27         | 32 | 14 | 27 |

AF = Width across flats

## Product versions

|                            |                                    |
|----------------------------|------------------------------------|
| <b>K 440-28 - K 440-47</b> | Connection socket, T shaped, Steel |
|----------------------------|------------------------------------|