

# K 44-52

Reducing connecting fitting, T shaped

## Properties

|                        |  |
|------------------------|--|
| <b>Connection 1</b>    | metric cylindrical outer thread              |
| <b>Sealing form 1</b>  | 24° inner cone                               |
| <b>Connection 2</b>    | metric cylindrical outer thread              |
| <b>Sealing form 2</b>  | Butt construction                            |
| <b>Connection 3</b>    | metric cylindrical outer thread              |
| <b>Sealing form 3</b>  | 24° inner cone                               |
| <b>Construction</b>    | T shaped                                     |
| <b>Scope of supply</b> | with union nut, cutting ring and counter nut |
| <b>Material</b>        | Steel  |
| <b>Surface</b>         | electro galvanised                           |



## Item

| Identification | d3<br>(mm) | G2         | Ø d2<br>(mm) | i2<br>(mm) | L1<br>(mm) | L2<br>(mm) | L3<br>(mm) | AF<br>(mm) | S1 | S2 | S3 |
|----------------|------------|------------|--------------|------------|------------|------------|------------|------------|----|----|----|
| <b>K 44-52</b> | 15         | M 22 x 1.5 | 6            | 25         | 28         | 33         | 33         | 27         | 27 | 14 | 27 |

AF = Width across flats

## Product versions

**K 440-37** Reducing connecting socket, T shaped, Steel