

# K 44-75 - K 44-169

Screw in fitting

**HANSA FLEX**

## Properties

<b>Connection 1</b>	metric cylindrical outer thread
<b>Sealing form 1</b>	with thread seal made up of pressure and cord ring
<b>Connection 2 + 3</b>	metric cylindrical outer thread
<b>Sealing form 2 + 3</b>	24° inner cone
<b>Construction</b>	T shaped
<b>Scope of supply</b>	with union nut, cutting ring, counter nut, pressure ring and cord ring
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Item

Identification	Ø d2 (mm)	Ø d3 (mm)	G1	D (mm)	i (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	AF (mm)	S1	S2	S3
<b>K 44-148</b>	12	6	M 16 x 1.5	21	21	24	32	17	37	17	22	22	14
<b>K 44-75</b>	12	-	M 16 x 1.5	21	20	24	32	17	37	17	22	22	22
<b>K 44-139</b>	12	-	M 22 x 1.5	27	24	26	34	19	42	17	22	27	22
<b>K 44-140</b>	8	-	M 22 x 1.5	27	24	26	34	19	42	17	17	27	17
<b>K 44-158</b>	10	-	M 22 x 1.5	27	24	26	34	19	42	17	19	27	19
<b>K 44-169</b>	10	-	M 16 x 1.5	21	20	24	32	17	37	14	19	22	19

Ø d2 = External pipe diameter – AF = Width across flats

## Product versions

**K 440-52 / K 440-127** Screw-in socket, T shaped, Steel