

K 44-75 - K 44-169

Screw in fitting

HANSA FLEX

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	with thread seal made up of pressure and cord ring
Connection 2 + 3	metric cylindrical outer thread
Sealing form 2 + 3	24° inner cone
Construction	T shaped
Scope of supply	with union nut, cutting ring, counter nut, pressure ring and cord ring
Material	Steel
Surface	electro galvanised



Item

Identification	Ø d2 (mm)	Ø d3 (mm)	G1	D (mm)	i (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	AF (mm)	S1	S2	S3
K 44-148	12	6	M 16 x 1.5	21	21	24	32	17	37	17	22	22	14
K 44-75	12	-	M 16 x 1.5	21	20	24	32	17	37	17	22	22	22
K 44-139	12	-	M 22 x 1.5	27	24	26	34	19	42	17	22	27	22
K 44-140	8	-	M 22 x 1.5	27	24	26	34	19	42	17	17	27	17
K 44-158	10	-	M 22 x 1.5	27	24	26	34	19	42	17	19	27	19
K 44-169	10	-	M 16 x 1.5	21	20	24	32	17	37	14	19	22	19

Ø d2 = External pipe diameter – AF = Width across flats

Product versions

K 440-52 / K 440-127 Screw-in socket, T shaped, Steel