

K 44-76 - K 44-160

Screw-in fitting, L shaped

HANSA FLEX

Properties

Connection 1	metric cylindrical outer thread
Sealing form 1	with thread seal made up of pressure and cord ring
Connection 2 + 3	metric cylindrical outer thread
Sealing form 2 + 3	24° inner cone
Construction	L shaped
Scope of supply	with union nut, cutting ring, counter nut, pressure ring and cord ring
Material	Steel
Surface	electro galvanised



Item

Identification	Ø d2 (mm)	Ø d3 (mm)	G1	D (mm)	i (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	AF (mm)	S1	S2	S3
K 44-120	6	12	M 16 x 1.5	21	24	24	32	17	38	17	22	14	22
K 44-76	12	-	M 16 x 1.5	21	20	28	36	21	35	17	22	22	22
K 44-142	12	8	M 22 x 1.5	27	24	24	32	17	42	17	17	22	27
K 44-149	12	-	M 22 x 1.5	27	24	24	32	17	42	17	22	22	27
K 44-121	8	12	M 16 x 1.5	21	24	24	32	17	38	17	22	17	22
K 44-157	10	-	M 22 x 1.5	27	24	24	32	17	42	17	19	19	27
K 44-160	10	-	M 16 x 1.5	21	24	24	32	17	40	14	19	19	22

Ø d2 = External pipe diameter – AF = Width across flats

Product versions

K 440-55 - K 440-122 Screw-in socket, L shaped, Steel