

# K 44-76 - K 44-160

Screw-in fitting, L shaped

**HANSA FLEX**

## Properties

<b>Connection 1</b>	metric cylindrical outer thread
<b>Sealing form 1</b>	with thread seal made up of pressure and cord ring
<b>Connection 2 + 3</b>	metric cylindrical outer thread
<b>Sealing form 2 + 3</b>	24° inner cone
<b>Construction</b>	L shaped
<b>Scope of supply</b>	with union nut, cutting ring, counter nut, pressure ring and cord ring
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Item

Identification	Ø d2 (mm)	Ø d3 (mm)	G1	D (mm)	i (mm)	L1 (mm)	L2 (mm)	L3 (mm)	L4 (mm)	AF (mm)	S1	S2	S3
K 44-120	6	12	M 16 x 1.5	21	24	24	32	17	38	17	22	14	22
K 44-76	12	-	M 16 x 1.5	21	20	28	36	21	35	17	22	22	22
K 44-142	12	8	M 22 x 1.5	27	24	24	32	17	42	17	17	22	27
K 44-149	12	-	M 22 x 1.5	27	24	24	32	17	42	17	22	22	27
K 44-121	8	12	M 16 x 1.5	21	24	24	32	17	38	17	22	17	22
K 44-157	10	-	M 22 x 1.5	27	24	24	32	17	42	17	19	19	27
K 44-160	10	-	M 16 x 1.5	21	24	24	32	17	40	14	19	19	22

Ø d2 = External pipe diameter – AF = Width across flats

## Product versions

K 440-55 - K 440-122 Screw-in socket, L shaped, Steel