

# K 440-105 / K 440-113

Connection socket, T shaped



| Properties         |                                 |
|--------------------|---------------------------------|
| Connection 1 - 3   | metric cylindrical outer thread |
| Sealing form 1 - 3 | 24° inner cone                  |
| Construction type  | without counter nut             |
| Design             | for bulkhead mounting           |
| Construction       | T shaped                        |
| Material           | Steel                           |
| Surface            | electro galvanised              |



| Item           |              |              |            |            |            |            |            |            |            |            |            |
|----------------|--------------|--------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| Identification | Ø d2<br>(mm) | Ø d3<br>(mm) | G1         | G2         | G3         | L1<br>(mm) | L2<br>(mm) | L3<br>(mm) | L4<br>(mm) | L5<br>(mm) | AF<br>(mm) |
| K 440-105      | 12           | -            | M 18 x 1.5 | M 18 x 1.5 | M 18 x 1.5 | 24         | 56         | 17         | 29         | 20         | 17         |
| K 440-113      | 12           | 10           | M 18 x 1.5 | M 16 x 1.5 | M 16 x 1.5 | 24         | 56         | 17         | 29         | 20         | 17         |

AF = Width across flats

| Product versions    |   |
|---------------------|---|
| K 44-156 / K 44-162 | Conection reduction fitting, T shaped, with union nut, cutting ring and counter nut |